

## Fire Service Connections

A fire service pumper connection, located outside buildings, permits the fire service to pump water into a sprinkler system from a nearby public hydrant or reservoir. Water supplied at high pressure will aid automatic sprinklers to control a fire. The connection may also be used to supply building standpipes.

FM Approved connections are made of bronze and consist of two inlet couplings threaded for standard fire hose and siamesed into an outlet pipe connection. A check valve is provided in each inlet so that either connection may be used separately. The connections are available in straight, 45° or 90° patterns. Unless otherwise noted in the listing, these connections have 175 psi (1205 kPa) rated working pressure.

### Fig. No. AFDC-100

#### Product Specification

Model No	Description	Nominal Size, Inlets x Outlet, in	Rated Working Pressure	
			psi	(kPa)
AFDC-100	Straightway Single Clapper	2 1/2 x 2 1/2 x 4	300	(2065)

<b>Company Name:</b>	Haci Ayvaz Endüstriyel Mamülleri San. ve Tic. A.S.
<b>Company Address:</b>	Atatürk Sanayi Bölgesi Mustafa Inan Cad. No: 44, 34555 Hadimköy-Istanbul, Turkey
<b>Company Website:</b>	<a href="http://www.ayvaz.com">http://www.ayvaz.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	Turkey
<b>Certification Type:</b>	FM Approved
<b>Class of Work:</b>	1530-Fire Department Connections