

VNIV.EX16097 - Sprinklers, Automatic and Open

Sprinklers, Automatic and Open

See General Information for Sprinklers, Automatic and Open

HACI AYVAZ ENDUSTRIYEL MAMULLER SAN VE TIC A.S.

EX16097

Hadimkoy Mahallesi

Mustafa Inan Caddesi No:44 Arvavutkoy

34555 istanbul, TURKEY

Sprinkler Identification Number (SIN), Glass Bulb Type AYVAZ AZ017, AYVAZ AZ 018, AYVAZ AZ001, AYVAZ AZ002, AYVAZ AZ 003, AYVAZ AZ 004, AYVAZ AZ 005, AYVAZ AZ 006, AYVAZ AZ 007, AYVAZ AZ 008.

AZ1010 ,AZ1020 ,AZ2010 ,AZ2020 ,AZ3010 ,AZ3020 ,AZ4010 ,AZ4020.

UPRIGHT AND PENDENT STANDARD SPRAY SPRINKLERS

NOMINAL 5.6 K - FACTOR

SIN	Response Type	Type	Nom K-Factor	System Working Pressure, psig	Temp Rating, °F
AYVAZ AZ 003	SR	Upright	5.6	175	135, 155, 175, 200
AYVAZ AZ 004	QR	Upright	5.6	175	135, 155, 175, 200
AYVAZ AZ 005	SR	Pendent	5.6	175	135, 155, 175, 200
AYVAZ AZ 006	QR	Pendent	5.6	175	135, 155, 175, 200

STANDARD SIDEWALL SPRAY SPRINKLERS

SIN	Response Type	Type	Nom K-Factor	System Working Pressure, psig	Temp Rating, °F
AYVAZ AZ001+#	SR	Horizontal	5.6	175	135, 155, 175, 200
AYVAZ AZ002+#	QR	Horizontal	5.6	175	135, 155, 175, 200
AYVAZ AZ017*#	SR	Horizontal	5.6	175	135, 155, 175, 200
AYVAZ AZ 018*#	QR	Horizontal	5.6	175	135, 155, 175, 200

+ - Installed 4 to 12 in. below ceiling.

* - Installed 4 to 6 in. below ceiling.

- For ordinary hazard occupancies.

FLUSH, RECESSED, AND CONCEALED SPRINKLERS

SIN	Response Type	Type	Nom K-Factor	Cover	Temp. Rating, °F
AYVAZ AZ 007	SR	Concealed	5.6	135, 155	135, 155, 175, 200
AYVAZ AZ 008	QR	Concealed	5.6	135, 155	135, 155, 175, 200

UPRIGHT AND PENDENT STANDARD SPRAY SPRINKLERS NOMINAL 5.6 K - FACTOR

SIN	Response Type	Type	Nom K-Factor	System Working Pressure, psig	Temp Rating, °F
AZ1010	SR	Upright	5.6	175	135, 155, 175, 200
AZ1020	QR	Upright	5.6	175	135, 155, 175, 200
AZ2010	SR	Pendent	5.6	175	135, 155, 175, 200
AZ2020	QR	Pendent	5.6	175	135, 155, 175, 200

STANDARD SIDEWALL SPRAY SPRINKLERS

SIN	Response Type	Type	Nom K-Factor	System Working Pressure, psig	Temp Rating, °F
AZ3010+#	SR	Horizontal	5.6	175	135, 155, 175, 200
AZ3020+#	QR	Horizontal	5.6	175	135, 155, 175, 200

+ - Installed 4 to 12 in. below ceiling.

- For ordinary hazard occupancies.

FLUSH, RECESSED, AND CONCEALED SPRINKLERS

SIN	Response Type	Type	Nom K-Factor	Temp. Rating, °F	
				Cover	Sprinkler
AZ4010	SR	Concealed	5.6	135, 155	135, 155, 175, 200
AZ4020	QR	Concealed	5.6	135, 155	135, 155, 175, 200

Last Updated on 2020-12-10

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"