

Trim Water Pressure Relief Valves (Adjustable)

An adjustable set pressure trim water pressure relief valve is a small valve designed to relieve pressure build-up in a sprinkler system or in valve trim. It is open to a drain line. Unless otherwise specified, rated working pressure is 175 psi (1205 kPa). The range of pressure setting is shown below.

Model 55L-60

Product Specification

| Model No | Valve Size | | Rated Working Pressure | | Remarks |
|--------------|------------|----------|------------------------|--------|------------|
| | in | (mm) | psi | (kPa) | Remarks |
| Model 55L-60 | 1/2, 3/4 | (15, 20) | 300 | (2065) | a, b, c, d |

Remarks:

a. Valve supplied with Female NPT inlet and outlet connection.

d. Not suitable for discharging the full rated pump capacity.

| Company Name: | Cla-Val Co. | |
|------------------------------|---|--|
| Company Address: | 1701 Placentia, Costa Mesa, California 92627, USA | |
| Company Website: | http://cla-val.com | |
| New/Updated Product Listing: | No | |
| Listing Country: | United States of America | |
| Certification Type: | FM Approved | |
| Class of Work: | 1359-Trim Water PRV (1/4th2-1/2) | |

b. Adjustable relief pressure settings from 0 to 75, 20 to 200, 100 to 300 and 20 to 300 psi (0 to 515, 140 to 1380, 690 to 2070 and 140 to 2070 kPa).

c. Approved when supplied with a stainless steel, bronze or brass valve body.